

TECHNICAL DATASHEET TURBOCAR

EXTREME – IG4




Illustrative purposes only; the model shown here could be different that one supplied

STANDARD EQUIPMENT


- High efficiency partial flow turbine drive directly coupled to the gearbox (minimum pressure losses in its category)
- 2 speed gearbox with oil lubrication
- Safety devices for PTO and rewinding out of the drum
- Moving transmission through toothed crown, which is placed close to the maximum stress point on the drum and not pushing against the hose reel borders
- Leadscrew driven hose layering guide
- By-pass “double action” for automatic speed control
- Glycerine filled pressure gauge
- Irrigamatic Computer B2 for hose speed control
- Huge diameter 360° turntable
- Hose emptying compressor
- Hot galvanised anti-sinking plate
- Hydraulic system for turntable rotation, trolley lift, drawbar jack and independent wheels lifting, actioned by distributor lever situated on one side of the machine
- Trolley lift and stacker legs driven by hydraulic pistons incorporated inside the structure
- Painted frame on twin-axle 4 wheels
- Hot galvanised steel pipework with double water inlet and components
- 2 wheels hot galvanised sprinkler trolley with adjustable track, height and legs
- Accident prevention protections according to CE standard
- Sprinkler with set of nozzles
- High resistant medium density PE hose with differentiated thickness
- Instructions and maintenance handbook
- CE Certificate
- Warranty certificate

Available Models

Structure	Model	Type	Hose ending	P.E. hose Ø (mm)	Hose length L (m)	Sprinkler
IG4D	125 IG 700	A	7	125	700	EXPLORER / TWIN 202
	125 IG 750	A	9	125	750	EXPLORER / TWIN 202
	135 IG 650	F	4	135	650	EXPLORER / TWIN 202
	140 IG 550	C	10	140	550	EXPLORER / TWIN 202
	140 IG 600	E	4	140	600	EXPLORER / TWIN 202
	150 IG 500	H	9	150	500	EXPLORER / TWIN 202
	160 IG 400	D	5	160	400	LANCER



Weight and overall dimensions



STR.	TYPE	WHEELS	A	B	B1	C	D	E	F	G	KG
IG4	A	11.5/80.15.3-6F	3580	4100	3730	2900	2750	3700	5300	7100	9300 ÷ 9800
	A	13.0/65.18-6F	3580	4120	3730	2990	2750	3700	5300	7100	
	A	15.0/55.17-8F	3580	4100	3730	3130	2750	3700	5300	7100	
	A	500/50.17-6F	3580	4140	3730	3330	2750	3700	5300	7100	
	B	11.5/80.15.3-6F	3580	4100	3730	2900	2750	3700	5300	7100	
	B	13.0/65.18-6F	3580	4120	3730	2990	2750	3700	5300	7100	
	B	15.0/55.17-8F	3580	4100	3730	3130	2750	3700	5300	7100	
	B	500/50.17-6F	3580	4140	3730	3330	2750	3700	5300	7100	
	C	11.5/80.15.3-6F	3580	4100	3730	2900	2750	3700	5300	7100	
	C	13.0/65.18-6F	3580	4120	3730	2990	2750	3700	5300	7100	
	C	15.0/55.17-8F	3580	4100	3730	3130	2750	3700	5300	7100	
	C	500/50.17-6F	3580	4140	3730	3330	2750	3700	5300	7100	
	D	11.5/80.15.3-6F	3580	4100	3730	2900	2750	3700	5300	7100	
	D	13.0/65.18-6F	3580	4120	3730	2990	2750	3700	5300	7100	
	D	15.0/55.17-8F	3580	4100	3730	3130	2750	3700	5300	7100	
	D	500/50.17-6F	3580	4140	3730	3330	2750	3700	5300	7100	
	E	11.5/80.15.3-6F	3580	4100	3730	2900	2750	3700	5300	7100	
	E	13.0/65.18-6F	3580	4120	3730	2990	2750	3700	5300	7100	
	E	15.0/55.17-8F	3580	4100	3730	3130	2750	3700	5300	7100	
	E	500/50.17-6F	3580	4140	3730	3330	2750	3700	5300	7100	
	F	11.5/80.15.3-6F	3580	4100	3730	2900	2750	3700	5300	7100	
	F	13.0/65.18-6F	3580	4120	3730	2990	2750	3700	5300	7100	
	F	15.0/55.17-8F	3580	4100	3730	3130	2750	3700	5300	7100	
	F	500/50.17-6F	3580	4140	3730	3330	2750	3700	5300	7100	
H	11.5/80.15.3-6F	3580	4100	3730	2900	2750	3700	5300	7100		
H	13.0/65.18-6F	3580	4120	3730	2990	2750	3700	5300	7100		
H	15.0/55.17-8F	3580	4100	3730	3130	2750	3700	5300	7100		
H	500/50.17-6F	3580	4140	3730	3330	2750	3700	5300	7100		

Technical Features

Ø hose (mm)	Ø nozzle (mm)	Machine pressure (atm)				Sprinkler press. (atm)	Throw (mt)	Irrigated width (mt)	Flow (l/min)	Irrigated area (ha)				Rainfall (mm)		
		700	750							700	750					
125	32	8,9	9,8			4,0	54,0	91,8	1282	6,44	6,87			79,5	26,5	15,9
		10,8	12,0			5,0	58,0	98,6	1432	6,94	7,41			82,3	27,4	16,5
	36	13,7	15,4			5,0	61,0	103,7	1813	7,32	7,81			98,9	33,0	19,8
		16,2	18,2			6,0	66,0	112,2	1988	7,96	8,49			99,7	33,2	19,9
	38	15,5	17,6			5,0	63,0	107,1	2022	7,57	8,08			106,5	35,5	21,3
		18,3	20,7			6,0	68,0	115,6	2215	8,21	8,76			107,6	35,9	21,5
135	34	650								650						
		9,3				5,0	59,0	100,3	1618	6,59				95,9	32,0	19,2
	11,0				6,0	64,0	108,8	1773	7,18				96,4	32,1	19,3	
	36	10,2				5,0	61,0	103,7	1813	6,83				103,8	34,6	20,8
		12,0				6,0	66,0	112,2	1988	7,42				104,6	34,9	20,9
	38	11,2				5,0	63,0	107,1	2022	7,06				111,8	37,3	22,4
13,2					6,0	68,0	115,6	2215	7,66				112,9	37,6	22,6	
140	34	550	600							550	600					
		8,1	8,4			5,0	59,0	100,3	1618	5,64	6,11			88,1	29,4	17,6
	9,5	9,9			6,0	64,0	108,8	1773	6,15	6,67			88,5	29,5	17,7	
	36	8,6	9,0			5,0	61,0	103,7	1813	5,84	6,33			95,3	31,8	19,1
		10,2	10,7			6,0	66,0	112,2	1988	6,36	6,89			96,0	32,0	19,2
	38	9,3	9,8			5,0	63,0	107,1	2022	6,05	6,55			102,6	34,2	20,5
11,0		11,6			6,0	68,0	115,6	2215	6,56	7,11			103,6	34,5	20,7	
150	36	500								500						
		7,5				5,0	61,0	103,7	1813	5,35				94,6	31,5	18,9
	8,8				6,0	66,0	112,2	1988	5,82				95,3	31,8	19,1	
	38	7,9				5,0	63,0	107,1	2022	5,54				101,9	34,0	20,4
		9,3				6,0	68,0	115,6	2215	6,02				102,7	34,2	20,5
	40	9,9				6,0	69,0	117,3	2455	6,11				112,1	37,4	22,4
10,6					6,5	71,0	120,7	2552	6,31				112,9	37,6	22,6	
160	38	400								400						
		7,0				5,0	65,0	110,5	2022	4,68				96,5	32,2	19,3
	8,3				6,0	69,5	118,2	2215	5,04				98,1	32,7	19,6	
	40	8,7				6,0	71,0	120,7	2455	5,16				106,2	35,4	21,2
		10,0				7,0	76,0	129,2	2648	5,56				106,2	35,4	21,2
	42	9,1				6,0	72,0	122,4	2705	5,24				115,2	38,4	23,0
10,5					7,0	77,5	131,8	2918	5,69				114,5	38,2	22,9	